



### PLATES

THICKNESS (mm)	TOLERANCE (mm) <sup>(1)</sup>	KG/PIECE <sup>(2)</sup>	PC 1000
Standard size 620 x 3000 mm <sup>(3)</sup>			
15	+0.3 +1.5	37.65	●
18		44.55	○
20		49.20	●
25		60.75	●
30	+0.5 +2.5	74.25	●
40		97.50	●
50		120.75	●
Other standard sizes 1000 mm <sup>(3)</sup>			

(1): tolerances according to DIN EN 15860  
(2): average weights of production  
(3): tolerances in length -0 / + 3%

### ROUND RODS

DIAMETERS (mm)	TOLERANCES (mm) <sup>(1)</sup>	KG/PIECE <sup>(2)</sup>	PC 1000
Standard length 3000 mm <sup>(3)</sup>			
6	+0.1 +0.4	0.11	○
8	+0.1 +0.5	0.20	○
10		0.30	●
12		0.45	○
16	+0.2 +0.9	0.79	○
20	+0.2 +1.2	1.21	●
22		1.48	○
25		1.89	○
28		2.37	○
30		2.70	●
32		3.06	○
36		3.90	○
40	+0.2 +1.6	4.80	●
45	+0.3 +2.0	6.12	○
50		7.50	●
56		9.36	○
60	+0.3 +2.5	10.83	●
65		12.66	○
70		14.64	○
75	+0.4 +3.0	16.89	○
80		19.17	●
90	+0.5 +3.4	24.27	○
100	+0.6 +3.8	29.97	○
110	+0.7 +4.2	36.30	○
120	+0.8 +4.6	43.20	●
125		46.80	○
130	+0.9 +5.4	50.85	○
140		58.80	○
150	+1.0 +5.8	67.50	○
160	+1.1 +6.3	76.95	○
170	+1.2 +7.4	87.15	○
180		97.50	○
190	+1.3 +8.5	109.05	○
200		120.45	○
Other standard lengths 1000 mm <sup>(3)</sup>			

(1): tolerances according to DIN EN 15860  
(2): average weights of production  
(3): tolerances in length -0 / + 3%